



# MATERIAL SAFETY DATA SHEET

## SECTION 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name:** LOCTITE EASY REPAIR INSTANT EPOXY (HARDENER)  
**Other Name:** EPOXY LIQUID 5 min HCQ-03 Part B  
**Proper Shipping Name:** None allocated  
**Product Code(s):** 1162941  
**Use:** Two-part epoxy based adhesive. LOCTITE EASY REPAIR INSTANT EPOXY (HARDENER) is used in conjunction with the RESIN.  
**Supplier:** HENKEL AUSTRALIA PTY. LIMITED ABN 82 001 302 996  
CONSUMER ADHESIVES  
36 Brand Drive, Thomastown, Vic, 3074. Tel: (03) 9463 3333  
24 HOUR EMERGENCY CONTACT NUMBER Tel: 1800 032 379

## SECTION 2. HAZARDS IDENTIFICATION

### STATEMENT OF HAZARDOUS NATURE:

Classified as hazardous according to the criteria of Safe Work Australia. This material has been classified as Irritant (Xi).

### Risk Phrase(s):

R36/38 Irritating to eyes and skin.

### Safety Phrase(s):

S24/25 Avoid contact with skin and eyes.  
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S28 After contact with skin, wash immediately with plenty of soap-suds.  
S37/39 Wear suitable gloves and eye/face protection.  
S46 If swallowed, seek medical advice immediately and show this container or label.

### DANGEROUS GOODS INFORMATION:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

**SUSDP POISON SCHEDULE:** 5

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

### INGREDIENTS:

CHEMICAL ENTITY	CAS NO.	PROPORTION
Polymercaptan	[72244-98-5]	> 60% w/w
Modified amine		10-<20%

## SECTION 4. FIRST AID MEASURES

**Ingestion:** If swallowed, **do not** induce vomiting. Seek medical attention or contact a Poisons Information Centre (Phone 13 11 26).

**Skin:** Remove contaminated clothing and wash affected areas with plenty of soap and water. If irritation occurs, seek medical attention.

**DATE OF ISSUE:** 27.07.10  
Page 1 of 4

**REVISION OF:** -  
PRODUCT NAME:

**IDH NO:** -  
LOCTITE EASY REPAIR EPOXY (HARDENER)



## MATERIAL SAFETY DATA SHEET

**Eyes:** Hold eyes open and flush with water for at least 15 minutes. Seek medical attention.

**Inhalation:** If inhaled, remove from contaminated area. For all but the most minor symptoms, arrange for patient to be seen by a doctor.

**Advice to doctor:** Treat symptomatically.

**First Aid facilities:** Eye wash and normal washroom facilities

### SECTION 5. FIRE FIGHTING MEASURES

**Suitable extinguishing media:** Carbon dioxide, foam, dry chemical, water fog

**Hazards from combustion products:** Combustible liquid. In a fire, it will emit oxides of carbon, oxides of sulphur, oxides of nitrogen and noxious fumes.

**Precautions for fire fighters and special protective equipment:** If there is a risk of exposure to products of combustion, then fire-fighters should wear full protective clothing and self-contained breathing apparatus.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Wear impervious gloves, chemical goggles and boots. For smaller spills, wipe up with a cloth. For larger spills, contain and collect spillage with inert absorbent materials (e.g. sand, earth, vermiculite) and transfer to sealable containers suitable for storing spilled material. Use a polar organic solvent to clean up areas in contact with spilled material. Prevent product from entering waterways. Dispose of residues in chemical waste disposal area in accordance with relevant State and Federal requirements.

### SECTION 7. HANDLING AND STORAGE

**Safe Handling:** Observe recommendations made under SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION. Wear impervious gloves and chemical splash goggles. Upon mixing hardener with resin, the adhesive will release heat and begin to cure. Do not cut or heat empty containers, as they may contain hazardous residues. If the cured material is cut or dry sanded, wear an approved particulate respirator.

**Storage:** Store indoors in a cool, dry, well ventilated area. Keep containers sealed when not in use. Protect from physical damage and direct sunlight. Store between 2°C and 45°C.

### SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**National exposure standards:** None established

**Engineering controls:** In confined areas, use a local mechanical exhaust system if vapour is being generated.

**Personal protective equipment:** Use good industrial hygiene. Avoid contact with skin and eyes. Wear overalls, safety footwear, impervious gloves and chemical splash goggles. Use in a well ventilated area. In poorly ventilated areas, wear a respirator complying with the requirements of AS 1715 and AS 1716.



## MATERIAL SAFETY DATA SHEET

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical data:**

Appearance:	Viscous liquid
Specific gravity:	1.0-1.1
Solubility:	Slightly soluble in water
Flash point:	>150°C
Odour:	Mercaptan
VOC content:	3.7%

### SECTION 10. STABILITY AND REACTIVITY

**Chemical stability:** Stable under normal conditions of temperature and pressure.

**Conditions to avoid:** Avoid heat and flames.

**Incompatible materials:** Keep away from acids, alkalis and strong oxidising agents.

**Hazardous decomposition products:** When heated to decomposition, it will emit oxides of carbon, oxides of sulphur, oxides of nitrogen and noxious fumes.

**Hazardous reactions:** Exothermic polymerisation will occur with epoxy resins.

### SECTION 11. TOXICOLOGICAL INFORMATION

**HEALTH EFFECTS:****Acute:**

Ingestion: If swallowed, this product will cause irritation to the mouth, throat and digestive tract.

Skin: Contact with the skin can result in irritation.

Eyes: Contact with the eyes can cause irritation.

Inhalation: Inhalation of vapour may cause irritation to the respiratory tract.

**Chronic:** Repeated skin contact may lead to dermatitis.

**Toxicity information:** None available.

### SECTION 12. ECOLOGICAL INFORMATION

No ecological information is available for this product. Do not contaminate waterways and soil.

### SECTION 13. DISPOSAL CONSIDERATIONS

Dispose of any unwanted material via chemical waste collections. Empty containers should be recycled or disposed of at an approved land waste site.

### SECTION 14. TRANSPORT INFORMATION

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

### SECTION 15. REGULATORY INFORMATION

SUSDP POISON SCHEDULE: 5



## MATERIAL SAFETY DATA SHEET

### SECTION 16. OTHER INFORMATION

**Abbreviations/acronyms:**

SUSDP - Standard for the Uniform Scheduling of Drugs and Poisons

**DISCLAIMER:**

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in this Material Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Material Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.